



RP-82

Compact Printer



Specification

Print	
Printing Method	Thermal Line
Printing Speed	200mm/s
Resolution	203dpi
Effective Printing Width	72mm & 48mm
Printing Setting	Support adjustment for the header margin, line space, receipt width and barcode height
RAM	96KB
FLASH	2MB
Character	
Character Set	ANK,GB18030(Chinese)
Print Font	ANK: 12 x24,9x17, Chinese: 24 x 24
Character per Line	48-font A/64-font B
Paper Spec	
Paper Type	Thermal paper
Paper Width	80mm
Paper Roll Diameter	Max: 80.0mm
Paper Supply Method	
Drop-in paper load	
Reliability	
MCBF	60 million lines
TPH	100km
Barcodes	
UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF, CODEBAR, CODE93, CODE128	
Emulation	
ESC/POS	
Driver	
XP, Win7, Win8, Win10, iOS, Android, Linux, MacOS	
Sensor	
Paper End Sensor; Paper Near End Sensor(Optional)	
Drawer Port	
RJ11	
Interface	
USB+LAN	
Network	
Wire	
TCP/IP Ethernet interface (10M/100M)	
Power Supply (Adapter)	
AC100 ~240V(± 10%) DC 24V, 2.5A	
Auto cutter	
Type	Straight Knife
Life	1,000,000 cuts
Physical	
Printer Dimension (WxLxH)	156 * 125 * 120mm
Environment parameters:	
Working temperature: -20°C~70°C Working humidity: 0°C~40°C	
Storing temperature: 5%~95% Storing humidity:20%~85%	
Remarks	
3PCS Orange light	
Normal: The light on	
Abnormal: The light flashes	
Applications:	
Restaurant, Department Store, Kitchen, Convenience Store, Specialty Retail, Super market	